

100 Series

Reverse Cottage Single-Hung Windows



		1'-6"	2'-0"	2'-6"	3'-0"	3'-6"	4'-0"
		(457)	(610)	(762)	(914)	(1067)	(1219)
Rough Opening	Unit Dimension	1'-5½"	1'-11½"	2'-5½"	2'-11½"	3'-5½"	3'-11½"
		(445)	(597)	(749)	(902)	(1054)	(1207)
1'-0"	(305)	1610	2010	2610	3010	3610	4010
1'-6"	(457)	1616	2016	2616	3016	3616	4016
2'-0"	(610)	1620	2020	2620	3020	3620	4020
2'-6"	(762)	1626	2026	2626	3026	3626	4026
3'-0"	(914)	1630	2030	2630	3030	3630	4030
3'-6"	(1067)	1636	2036	2636	3036	3636	4036
4'-0"	(1219)	1640	2040	2640	3040	3640	4040
4'-6"	(1372)	1646	2046	2646	3046	3646	4046
5'-0"	(1524)	1650	2050	2650+	3050+	3650+	4050+
5'-6"	(1676)	1656	2056	2656+	3056+	3656+	4056+
5'-5½"	(1664)						
4'-11½"	(1511)						
4'-5½"	(1359)						

Single Transoms (100REC)

1610	2010	2610	3010	3610	4010
1616	2016	2616	3016	3616	4016
1620	2020	2620	3020	3620	4020

Reverse Cottage Single-Hung Windows (100SHS RC)

1626	2026	2626	3026	3626	4026
1630	2030	2630	3030	3630	4030
1636	2036	2636	3036	3636	4036
1640	2040	2640	3040	3640	4040
1646	2046	2646	3046	3646	4046
1650	2050	2650+	3050+	3650+	4050+
1656	2056	2656+	3056+	3656+	4056+

Taller sizes continue on page 02

Reverse cottage windows with a height of 6'-5 ½" (1969) and smaller have a 3:2 ratio.

Reverse cottage windows with a height greater than 6'-5 ½" (1969) are only available with a 2:1 ratio.

Notes:

"Window Dimension" always refers to outside frame to frame dimension.

"Minimum Rough Opening" dimensions may need to be increased to allow for use of building wraps, flashing, sill panning, brackets, fasteners or other items.

Dimensions in parentheses are in millimeters.

♦ Meet or exceed clear opening area of 5.7 sq. ft. or 0.53 m², clear opening width of 20" (508) and clear opening height of 24" (610).

+ Drywall Pass Through Window available for these standard and reverse cottage sizes and for custom-size windows wider than 1'-11 ½" (597) and taller than 4'-5 ½" (1359).

Date: 07/08/16

Scale: 1/8" (3) = 1' (305)

100 Series



Reverse Cottage Single-Hung Windows

		1'-6"	2'-0"	2'-6"	3'-0"	3'-6"	4'-0"
		(457)	(610)	(762)	(914)	(1067)	(1219)
		1'-5½"	1'-11½"	2'-5½"	2'-11½"	3'-5½"	3'-11½"
		(445)	(597)	(749)	(902)	(1054)	(1207)
		Continuation from page 01					
Rough Opening	Unit Dimension	[Diagrammatic Window Grid]					
		1660	2060	2660 †	3060 ††	3660 ††	4060 ††
6'-0"	(1829)	[Diagrammatic Window Grid]					
		1666	2066	2666 †	3066 ††	3666 ††	4066 ††
6'-6"	(1981)	[Diagrammatic Window Grid]					
		1670	2070	2670 †	3070 †	3670 ††	4070 ††
7'-0"	(2134)	[Diagrammatic Window Grid]					
		1676	2076	2676 †	3076 ††	3676 ††	4076 ††
7'-6"	(2286)	[Diagrammatic Window Grid]					

Reverse cottage windows with a height of 6'-5 ½" (1969) and smaller have a 3:2 ratio.

Reverse cottage windows with a height greater than 6'-5 ½" (1969) are only available with a 2:1 ratio.

Notes:

"Window Dimension" always refers to outside frame to frame dimension.

"Minimum Rough Opening" dimensions may need to be increased to allow for use of building wraps, flashing, sill panning, brackets, fasteners or other items.

Dimensions in parentheses are in millimeters.

♦ Meet or exceed clear opening area of 5.7 sq. ft. or 0.53 m², clear opening width of 20" (508) and clear opening height of 24" (610).

† Drywall Pass Through Window available for these standard and reverse cottage sizes and for custom-size windows wider than 1'-11 ½" (597) and taller than 4'-5 ½" (1359).

Date: 07/08/16

Scale: 1/8" (3) = 1' (305)