


E-Series

Direct Glazed Sidelights
Commercial Door Sizes



Notes:




































































































"Unit Dimension" always refers to outside frame to frame dimension.
"Rough Opening" dimensions may need to be increased to allow for use of building wraps, flashing, sill panning, brackets, fasteners or other items.
Dimensions in parentheses are in millimeters.

Date: 1/17/17
Scale: 1/8" (3) = 1' (305)

E-Series

Direct Glazed Transoms
Commercial Door Sizes



Rough Opening	1'-3"	1'-5"	1'-7"	1'-9"	2'-1"	2'-7"	2'-9"	3'-1"	3'-3"	4'-0 ⁹ / ₁₆ "	5'-0 ⁹ / ₁₆ "
	(381)	(432)	(483)	(533)	(635)	(787)	(838)	(940)	(991)	(1233)	(1538)
Unit Dimension	1'-2 ¹ / ₂ "	1'-4 ¹ / ₂ "	1'-6 ¹ / ₂ "	1'-8 ¹ / ₂ "	2'-0 ¹ / ₂ "	2'-6 ¹ / ₂ "	2'-8 ¹ / ₂ "	3'-0 ¹ / ₂ "	3'-2 ¹ / ₂ "	4'-0 ¹ / ₁₆ "	5'-0 ¹ / ₁₆ "
	(368)	(419)	(470)	(521)	(622)	(775)	(826)	(927)	(978)	(1221)	(1526)
Outswing Direct Glazed Transom (HPODT)											
1'-2 ¹ / ₂ "											
1'-4 ¹ / ₂ "											
1'-6 ¹ / ₂ "											
1'-8 ¹ / ₂ "											
2'-0 ¹ / ₂ "											
2'-4 ¹ / ₂ "											
2'-6 ¹ / ₂ "											
2'-8 ¹ / ₂ "											
3'-0 ¹ / ₂ "											

Wider sizes continue on page 03

Wider sizes continue on page 03

Notes:

"Unit Dimension" always refers to outside frame to frame dimension.
"Rough Opening" dimensions may need to be increased to allow for use of building wraps, flashing, sill panning, brackets, fasteners or other items.
Dimensions in parentheses are in millimeters.

Date: 1/17/17
Scale: 1/8" (3) = 1' (305)

E-Series

Direct Glazed Transoms
Commercial Door Sizes



Rough Opening		5'-4 $\frac{9}{16}$ " (1640)	6'-0 $\frac{9}{16}$ " (1843)	6'-4 $\frac{9}{16}$ " (1945)
Unit Dimension		5'-4 $\frac{1}{16}$ " (1627)	6'-0 $\frac{1}{16}$ " (1830)	6'-4 $\frac{1}{16}$ " (1932)
Outswing Direct Glazed Transom (HPODT)				
1'-2 $\frac{1}{2}$ " (368)		HPODT5412	HPODT6012	HPODT6412
1'-4 $\frac{1}{4}$ " (419)		HPODT5414	HPODT6014	HPODT6414
1'-6 $\frac{1}{4}$ " (470)		HPODT5416	HPODT6016	HPODT6416
1'-8 $\frac{1}{4}$ " (521)		HPODT5418	HPODT6018	HPODT6418
2'-0 $\frac{1}{2}$ " (622)		HPODT5420	HPODT6020	HPODT6420
2'-4 $\frac{1}{4}$ " (724)		HPODT5424	HPODT6024	HPODT6424
2'-6 $\frac{1}{2}$ " (775)		HPODT5426	HPODT6026	HPODT6426
2'-8 $\frac{1}{2}$ " (826)		HPODT5428	HPODT6028	HPODT6428
3'-0 $\frac{1}{2}$ " (927)		HPODT5430	HPODT6030	HPODT6430

Continuation from page 02

Notes:

"Unit Dimension" always refers to outside frame to frame dimension.

"Rough Opening" dimensions may need to be increased to allow for use of building wraps, flashing, sill panning, brackets, fasteners or other items.

Dimensions in parentheses are in millimeters.

Date: 1/17/17
Scale: 1/8" (3) = 1' (305)