

BAY & BOW WINDOWS

Table of Casement 30° Angle Bay Windows

Projection		13 3/4" (349)	13 3/4" (349)	13 3/4" (349)	13 3/4" (349)	13 3/4" (349)
WIDTHS						
HEIGHTS	Window Dimension	5'-10" (1778)	7'-9 7/8" (2384)	7'-9 7/8" (2384)	9'-9 3/4" (2991)	9'-9 3/4" (2991)
	Minimum Rough Opening	5'-9 1/8" (1756)	7'-9" (2362)	7'-9" (2362)	9'-8 7/8" (2969)	9'-8 7/8" (2969)
	3'-1 7/16" (951)	30-C13-20	30-C23-20	30-P4030-20	30-C33-20	30-P6030-20
	3'-2" (965)					
	3'-6 5/16" (1075)	30-C135-20	30-C235-20	30-P4035-20	30-C335-20	30-P6035-20
	3'-6 7/8" (1089)					
	4'-1 1/2" (1257)	30-C14-20	30-C24-20	30-P4040-20	30-C34-20	30-P6040-20
	4'-2" (1270)					
	4'-6 5/16" (1380)	30-C145-20	30-C245-20	30-P4045-20	30-C345-20	30-P6045-20
	4'-6 7/8" (1394)					
	5'-1 3/8" (1559)	30-C15-20	30-C25-20	30-P4050-20	30-C35-20	30-P6050-20
	5'-1 7/8" (1572)					
	5'-6 5/16" (1684)	30-C155-20	30-C255-20	30-P4055-20		
	5'-6 7/8" (1699)					
	6'-1 3/8" (1864)	30-C16-20	30-C26-20	30-P4060-20		
	6'-1 7/8" (1876)					

Table of Casement 45° Angle Bay Windows

Projection		19 3/16" (487)	19 3/16" (487)	19 3/16" (487)	19 3/16" (487)	19 3/16" (487)
WIDTHS						
HEIGHTS	Window Dimension	5'-4 1/8" (1629)	7'-3 7/8" (2232)	7'-3 7/8" (2232)	9'-3 3/4" (2838)	9'-3 3/4" (2838)
	Minimum Rough Opening	5'-2 5/8" (1591)	7'-2 1/2" (2197)	7'-2 1/2" (2197)	9'-2 3/8" (2804)	9'-2 3/8" (2804)
	3'-1 7/16" (951)	45-C13-20	45-C23-20	45-P4030-20	45-C33-20	45-P6030-20
	3'-2" (965)					
	3'-6 5/16" (1075)	45-C135-20	45-C235-20	45-P4035-20	45-C335-20	45-P6035-20
	3'-6 7/8" (1089)					
	4'-1 1/2" (1257)	45-C14-20	45-C24-20	45-P4040-20	45-C34-20	45-P6040-20
	4'-2" (1270)					
	4'-6 5/16" (1380)	45-C145-20	45-C245-20	45-P4045-20	45-C345-20	45-P6045-20
	4'-6 7/8" (1394)					
	5'-1 3/8" (1559)	45-C15-20	45-C25-20	45-P4050-20	45-C35-20	45-P6050-20
	5'-1 7/8" (1572)					
	5'-6 5/16" (1684)	45-C155-20	45-C255-20	45-P4055-20		
	5'-6 7/8" (1699)					
	6'-1 3/8" (1864)	45-C16-20	45-C26-20	45-P4060-20		
	6'-1 7/8" (1876)					

Custom-size windows are available in 1/8" (3) increments.



⚠ WARNING

Proper support of projecting bow and bay windows is required, see installation guidelines. Failure to do so may result in injury, product damage and/or property damage.

In addition to venting shown in tables, other standard configurations are available. Choose left venting, right venting or stationary as viewed from the exterior.

- "Projection" refers to outside of the exterior sheathing to the outer edge of the window.
- "Window Dimension" always refers to outside frame to frame dimension.
- "**Minimum Rough Opening**" dimensions may need to be increased to allow for use of building wraps, flashing, sill panning, brackets, fasteners or other items.
- One Andersen cable kit is included with the unit for proper installation. Each cable supports a maximum load of 500 lbs. or 227 kg; additional support is necessary for loads exceeding 500 lbs. or 227 kg.
- Angle bay and bow windows include only the basic unit. Roof and other installation materials provided by other manufacturers.
- For walkout angle bay and bow window details and installation guidelines, contact your Andersen supplier or visit our website at andersenwindows.com/afd.
- Dimensions in parentheses are in millimeters.

Table of Casement 90° Box Bay Windows

		Projection 22 15/16" (583)		Projection 22 15/16" (583)		Projection 22 15/16" (583)		Projection 22 15/16" (583)	
WIDTHS									
	Window Dimension	4'-8 1/4" (1429)	4'-8 1/4" (1429)	6'-8 1/8" (2035)	6'-8 1/8" (2035)	6'-8 1/8" (2035)	6'-8 1/8" (2035)	6'-8 1/8" (2035)	6'-8 1/8" (2035)
HEIGHTS	Minimum Rough Opening	4'-1 5/8" (1260)	4'-1 5/8" (1260)	6'-1 1/2" (1867)	6'-1 1/2" (1867)	6'-1 1/2" (1867)	6'-1 1/2" (1867)	6'-1 1/2" (1867)	6'-1 1/2" (1867)
	3'-1 7/16" (951)	90-C23-15	90-P4030-15	90-C33-15	90-P6030-15	90-C33-15	90-P6030-15	90-C33-15	90-P6030-15
	3'-2" (965)	90-C235-15	90-P4035-15	90-C335-15	90-P6035-15	90-C335-15	90-P6035-15	90-C335-15	90-P6035-15
	3'-6 5/16" (1075)	90-C24-15	90-P4040-15	90-C34-15	90-P6040-15	90-C34-15	90-P6040-15	90-C34-15	90-P6040-15
	3'-6 7/8" (1089)	90-C245-15	90-P4045-15	90-C345-15	90-P6045-15	90-C345-15	90-P6045-15	90-C345-15	90-P6045-15
	4'-1 1/2" (1257)	90-C25-15	90-P4050-15	90-C35-15	90-P6050-15	90-C35-15	90-P6050-15	90-C35-15	90-P6050-15
	4'-2" (1270)	90-C255-15	90-P4055-15						
	4'-6 5/16" (1380)								
	4'-6 7/8" (1394)								
	5'-1 3/8" (1559)								
	5'-1 7/8" (1572)								
	5'-6 5/16" (1684)								
	5'-6 7/8" (1699)								
	6'-1 3/8" (1864)								
6'-1 7/8" (1876)									



Custom-size windows are available in 1/8" (3) increments.

In addition to venting shown in tables, other standard configurations are available. Choose left venting, right venting or stationary as viewed from the exterior.

Table of Casement 10° Bow Windows

		Projection 5 9/16" (141)		Projection 9 13/16" (249)		Projection 14" (356)		Projection 20 5/16" (516)		Projection 26 3/8" (670)		
WIDTHS												
	Window Dimension	6'-1 9/16" (1868)	8'-1 9/16" (2478)	10'-0 3/4" (3067)	11'-11 1/16" (3634)	11'-11 1/16" (3634)	11'-11 1/16" (3634)	11'-11 1/16" (3634)	11'-11 1/16" (3634)	13'-8 5/16" (4174)	13'-8 5/16" (4174)	
HEIGHTS	Minimum Rough Opening	6'-1 5/8" (1862)	8'-1 3/8" (2473)	10'-0 3/8" (3058)	11'-10 1/2" (3620)	11'-10 1/2" (3620)	11'-10 1/2" (3620)	11'-10 1/2" (3620)	11'-10 1/2" (3620)	13'-7 1/2" (4153)	13'-7 1/2" (4153)	
	3'-1 7/16" (951)	C33 BOW	C43 BOW	C53 BOW	C63 BOW	C63 BOW	C63 BOW	C63 BOW	C63 BOW	C73 BOW	C73 BOW	
	3'-2" (965)	C335 BOW	C435 BOW	C535 BOW	C635 BOW	C635 BOW	C635 BOW	C635 BOW	C635 BOW	C735 BOW	C735 BOW	
	3'-6 5/16" (1075)	C34 BOW	C44 BOW	C54 BOW	C64 BOW	C64 BOW	C64 BOW	C64 BOW	C64 BOW	C74 BOW	C74 BOW	
	3'-6 7/8" (1089)	C345 BOW	C445 BOW	C545 BOW	C645 BOW	C645 BOW	C645 BOW	C645 BOW	C645 BOW	C745 BOW	C745 BOW	
	4'-1 1/2" (1257)	C35 BOW	C45 BOW	C55 BOW	C65 BOW	C65 BOW	C65 BOW	C65 BOW	C65 BOW	C75 BOW	C75 BOW	
	4'-2" (1270)	C355 BOW	C455 BOW	C555 BOW	C655 BOW	C655 BOW	C655 BOW	C655 BOW	C655 BOW	C755 BOW	C755 BOW	
	4'-6 5/16" (1380)											
	4'-6 7/8" (1394)											
	5'-1 3/8" (1559)											
	5'-1 7/8" (1572)											
	5'-6 5/16" (1684)											
	5'-6 7/8" (1699)											
	6'-1 3/8" (1864)											
6'-1 7/8" (1876)												

⚠ WARNING

Proper support of projecting bow and bay windows is required, see installation guidelines. Failure to do so may result in injury, product damage and/or property damage.

- "Projection" refers to outside of the exterior sheathing to the outer edge of the window.
- "Window Dimension" always refers to outside frame to frame dimension.
- "**Minimum Rough Opening**" dimensions may need to be increased to allow for use of building wraps, flashing, sill panning, brackets, fasteners or other items.
- One Andersen cable kit is included with the unit for proper installation. Each cable supports a maximum load of 500 lbs. or 227 kg; additional support is necessary for loads exceeding 500 lbs. or 227 kg.
- Angle bay and bow windows include only the basic unit. Roof and other installation materials provided by other manufacturers.
- For walkout angle bay and bow window details and installation guidelines, contact your Andersen supplier or visit our website at andersenwindows.com/afd.
- Dimensions in parentheses are in millimeters.